

DECLARATION OF PERFORMANCE

No: DoP_K800_ENG_2013-001

1. Product type unique identification code:

K815, K816, K825, K826, K835 and K836
All models can have options with automatic supply air damper.

2. Intended use:

Fireplace for heating and comfort for connection to Fluegaspipe/Chimney.

3. Manufacturer:

Keddy AB, Box 542, 44115 Alingsås, telephone +46 322 78180

4. Authorised representatives:

-

5. The system or systems of assessment and continuous monitoring of product performance:

System 3.

6a. Harmonized standard:


SS-EN 13240: 2001, SS-EN 13240/A2: 2004/AC: 2006
Notified body nr: 1625 Rhein – Ruhr Feuerstätten Prüfstelle.
Report nr: RRF - 40 11 2860

7. Essential characteristics:

Specified performance for these products: K815, K816, K825, K826, K835 och K836

Essential feature	Performance
Fire safety	Pass
Flue gas temperature	254 °C
Fluepipe spigot	Pass (40mm)
Other fire characteristics. (eg risk of falling embers)	Pass
Discharge of combustion products	
CO - emission	0,10%
Flue gas Channel	Pass
Release of hazardous substances	NPD
Surface temperature	
Distance to combustible rear	10cm
Distance to combustible side	63cm
Fuel storage location	Pass
Temperature handle	Pass with use of glove
Mechanical strength (to support fluepipe/chimney)	Pass
Thermal effect	
Thermal effect	6,6 kW (4-9kW)
Efficiency	80%

Signed for and on behalf of the manufacturer by:



 Jonas Bodin
 Development Manager, Keddy AB
 Alingsås 2015-09-03

