

DECLARATION OF PERFORMANCE



No: DoP_SK2000_ENG_2015-001

1. Product type unique identification code:

Insert SK2000

2. Intended use:

Insert fireplace for heating and comfort for connection to Fluegaspipe/Chimney.

3. Manufacturer:

Keddy AB, Box 542, 44115 Alingsås, telephone +46 322 78180

4. Authorised representatives:

-

5. The system or systems of assessment and continuous monitoring of product performance:

System 3.

6a. Harmonized standard:


**SS-EN 13229: 2001/AC:2006 and EN 13229:2001/A2:2004/AC:2007
Anmält provningsorgan nr: 1625 Rhein – Ruhr Feuerstätten Prüfstelle.
Rapport nr: RRF – 29 14 3550**

7. Essential characteristics:

Specified performance for these products: SK2001 and SK2002

Essential feature	Performance
Fire safety	Pass
Flue gas temperature	225 °C
Fluepipe spigot	Pass (40mm)
Other fire characteristics. (eg risk of falling embers)	Pass
Discharge of combustion products	
CO - emission	0,10%
Flue gas Channel	Pass
Release of hazardous substances	NPD
Surface temperature	
Distance to combustible rear	3 cm (surrounding walls in noncombustible material with MIN thickness of 10cm. See installation instructions)
Distance to combustible side	3 cm (surrounding walls in noncombustible material with MIN thickness of 10cm. See installation instructions)
Fuel storage location	Pass
Temperature handle	Pass with use of glove
Mechanical strength (to support fluepipe/chimney)	Pass
Thermal performance	
Thermal effect	6,7 kW
Efficiency	83 %

Signed for and on behalf of the manufacturer by:


Jonas Bodin
Development Manager, Keddy AB
Alingsås 2015-09-03



Document created 20150916 Rev 03

Art: 193076